



 Lexmark™ |  GO Line™

B3442dw

Productivity. Reliability. Security.



B3442dw

Light, compact, and fast, the B3442dw supports output up to 40 pages per minute* with wired and wireless connectivity. Available Extra High Yield Unison™ toner prints up to 6,000 pages** and optional 550-sheet tray support longer print runs. A 1-GHz multi-core processor powers through big jobs, while Lexmark full-spectrum security helps protect sensitive information.

Speedy, compact printing

- ▶ Get monochrome output at up to 40 pages per minute*, with a first page as fast as 5.9 seconds.
- ▶ Tackle your printing workload with the power of a 1-GHz dual-core processor and 256 MB of memory.
- ▶ Compact dimensions of 222 mm high x 368 mm wide x 363 mm deep helps it fit almost anywhere.

Connect and control

- ▶ Connect via Wi-Fi, Ethernet, or USB.
- ▶ Simplify mobile printing via Lexmark Mobile Print app, as well as Google Cloud Print, Mopria® and AirPrint technologies.
- ▶ Two-line display lets you configure, interact with, and monitor vital system information.

Sustained output, enduring quality

- ▶ Available Extra High Yield Unison™ toner provides up to 6,000 pages** of output for more printing and less downtime.
- ▶ Optional paper tray increases total input capacity to 900

sheets to support longer print runs and enhanced media flexibility.

- ▶ Steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device, over the network, and everywhere in between.
- ▶ A range of embedded features harden the device against attacks.
- ▶ Standard Confidential Print feature helps ensure output security via simple PIN.

Save paper, save energy

- ▶ Automatic two-sided printing is standard.
- ▶ Built-in energy-saving modes help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous mono declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19752. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.



- | | | | | | |
|---|--|---|---|---|----------|
| 1 | Printer with 2-line display 222 x 368 x 363 mm | 3 | 250-Sheet tray Dimensions included as part of base model |  | Standard |
| 2 | 100-Sheet multipurpose feeder Dimensions included as part of base model | 4 | 550-Sheet Tray 107 x 370 x 378 mm |  | Optional |

| Product Specifications | | Lexmark B3442dw |
|--|---|-----------------|
| Printing | | |
| Display | 2-line LCD display | |
| Print Speed | Up to: Black: 40 ppm ¹ (A4) | |
| Time to First Page | As fast as: Black: 5.9 seconds ³ | |
| Print Resolution | Black: 2400 iQ (2400 x 600 dpi), 600 x 600 dpi | |
| Memory | (Standard): 256 MB / Maximum: 256 MB | |
| Hard Disk | # of slots: 1 | |
| Recommended Monthly Page Volume | 800 - 8000 pages ² | |
| Maximum Monthly Duty Cycle | Up to: 80000 pages per month ³ | |
| Supplies⁴ | | |
| Cartridge | up to: 3,000 ⁵ -page High Yield Cartridge / up to: 6,000 ⁵ -page Extra High Yield Cartridge / up to: 1,500 ⁵ -page Cartridge | |
| Imaging Unit | Up to: 40000 pages, based on 3 average letter-size pages per print job and ~ 5% coverage ⁶ | |
| Cartridge (with Shipping) | 3,000 ⁵ -page Return Program Toner Cartridge | |
| Paper Handling | | |
| Included Paper Handling | 100-Sheet Tray; 2-sided printing, 150-Sheet Output Bin, 250-Sheet Input | |
| Optional Paper Handling | 550-Sheet Tray; 550-Sheet Tray | |
| Input Capacity | Up to: (Standard): 350 pages 75 gsm bond / Maximum: 900 pages 75 gsm bond | |
| Output Capacity | Up to: (Standard): 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond | |
| Media Types Supported | Paper Labels, Continuous, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide | |
| Media Sizes Supported | A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, Letter 5 Envelope, Statement, Executive, DL Envelope, Folio, 10 Envelope | |
| General Information⁷ | | |
| Connectivity | 802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed (Type B), Ethernet 10/100Base-T (RJ-45) | |
| Sound | Printing: 53 dBA (Print) | |
| Operating Environment | Humidity: 8 to 80% RH / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 meters | |
| Warranty | 1 Year Limited Hardware Warranty | |
| Dimensions (W x H x D) | 222 x 368 x 363 mm / 9.3 x 14.5 x 14.3 inches | |
| Energy Star | TEC: 0.47 kWh per page | |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 (Copy) (ESA). For more information see: [www.lexmark.com/ISOspeeds](#).
² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies, paper loading, paper handling, speed, and throughput. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of productivity in relation to other Lexmark printers and MFPs. ⁴ "High Yield" functions only with remanufactured cartridges designed for use in a specific geographic region. See [www.lexmark.com/regions](#) for more details. ⁵ Average standard page yield value declared in accordance with ISO/IEC 19752. ⁶ Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, and print job characteristics. ⁷ "Energy Star" products are sold subject to certain conditions. See [www.lexmark.com/energy](#) for details.

Printzone.

1300 782 636

© 2020 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. Google Cloud Print is a trademark of Google, LLC. MOPRIA™, the Mopria™ Logo® and the Mopria™ Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT™ is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

