



---

# Lexmark CX730de

Color and Performance

---



## Lexmark CX730de

The Lexmark CX730de is designed for performance, security, and ease of use for mid-to-large workgroups at speeds up to 42 pages per minute\*. Single-pass two-sided scanning and a 7-inch (17.8 cm) tablet-like touchscreen make handling your tasks easy. Replacement cartridges with Unison™ Toner yield up to 22,000/10,500 black/color pages\*\* to keep you going.

### Robust, enduring quality

- ▶ Enjoy high-quality color output in a wide variety of environments—from back-office to retail to harsh manufacturing conditions.
- ▶ Intentionally engineered to last seven years or more with durable steel frames and long-life components.
- ▶ Unison™ Toner replacement cartridges yield up to 22,000/10,500 black/color pages\*\*.

### Make a statement with professional color

Enjoy the benefits of vibrant, professional-quality output allowing you to do more color printing in-house—saves time and money. Match corporate colors on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Color Replacement.



### Always easy. Always intuitive.

- ▶ Large, tablet-like, button-free touchscreens help you intuitively complete every task, from the basic to the complex.

- ▶ Get into the flow with standard access to built-in MFP workflow solutions like Scan Center, an easy-to-use app that simplifies routing to multiple destinations simultaneously.
- ▶ Plus, you can add other Lexmark or third-party partner solutions that meet your specific business needs.

### Secure by design

- ▶ Lexmark security features help keep your information safe—in the document, on the device, over the network and at all points in between.
- ▶ Always improving security, we now include a standard Trusted Platform Module\*\*\*, which delivers authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint.

### Sustainability matters

- ▶ Designed for the circular economy.
- ▶ Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The award-winning Lexmark Cartridge Collection Program (LCCP) and Lexmark Equipment Collection Program (LECP) minimize waste and support recycling (availability varies by country).

### Power up with IoT

- ▶ Sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- ▶ When you connect your device to Lexmark Cloud Services, you can optimize performance and uptime with additional features like predictive service and automatic supplies replenishment.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous black or continuous composite color (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Program (LCCP).

\*\*\* The Trusted Platform Module (TPM) is not available in some countries.

# Lexmark CX730de



- 1** Multifunction product with 7-inch (17.8 cm) touch screen  
24.44 x 18.85 x 20.9 in.  
621 x 479 x 533 mm
- 2** 550-Sheet tray with 100-sheet multipurpose feeder  
Dimensions included as part of base model
- 3** 550-Sheet Tray  
4.7 x 18.23 x 19 in.  
119 x 463 x 483 mm
- 4** 550-Sheet Tray  
4.7 x 18.23 x 19 in.  
119 x 463 x 483 mm

- 5** 550-Sheet Tray  
4.7 x 18.23 x 19 in.  
119 x 463 x 483 mm
- 6** 550-Sheet Tray  
4.7 x 18.23 x 19 in.  
119 x 463 x 483 mm
- 7** Adjustable Stand  
20.5 x 25.7 x 24.6 in.  
521 x 653 x 625 mm
- 8** Convenience Stapler LV  
3.23 x 4.29 x 4.77 in.

Standard  
 Optional

<b>P/N</b> 47C9500	<b>Hardware</b> Lexmark CX730de
<b>P/N</b> 71C0H10	<b>Supplies</b> Lexmark CS730, 735, CX730 Black 22K Toner Cartridge
71C0H20	Lexmark CS/CX730 Cyan 10.5K Toner Cartridge
71C0H30	Lexmark CS/CX730 Magenta 10.5K Toner Cartridge
71C0H40	Lexmark CS/CX730 Yellow 10.5K Toner Cartridge
71C0W00	Lexmark CS/CX730, 735, C/XC4342, C4352 170K Waste Container
71C0Z10	Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Black 150K Imaging Unit
71C0Z50	Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Color (CMY) 150K Imaging Unit
71C10C0	Lexmark CS/CX730, 735 Cyan Return Program 5K Toner Cartridge
71C10K0	Lexmark CS/CX730, 735 Black Return Program 5K Toner Cartridge
71C10M0	Lexmark CS/CX730, 735 Magenta Return Program 5K Toner Cartridge
71C10Y0	Lexmark CS/CX730, 735 Yellow Return Program 5K Toner Cartridge
71C1HC0	Lexmark CS/CX730 Cyan Return Program 10.5K Toner Cartridge
71C1HK0	Lexmark CS730, 735, CX730 Black Return Program 22K Toner Cartridge
71C1HM0	Lexmark CS/CX730 Magenta Return Program 10.5K Toner Cartridge
71C1HY0	Lexmark CS/CX730 Yellow Return Program 10.5K Toner Cartridge

<b>P/N</b> 40C2100	<b>Paper Handling</b> 550-Sheet Tray
47C4500	Convenience Stapler
<b>P/N</b> 27X0400	<b>Memory Options</b> 500+ GB Hard Disk
57X0070	Removable Hard Disk Enclosure Kit
57X9528	Intelligent Storage Device (ISD)

<b>P/N</b> 57X0300	<b>Application Solutions</b> Contact Authentication Device
57X0301	Contactless Authentication Device
82S1203	IPDS License
82S1204	Bar Code License

<b>P/N</b> 1021294	<b>Connectivity</b> USB Cable (2-meter)
27X0823	MarkNet N8370 Wireless for CS720, CS725, CX725
27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server
37X6350	Analog Fax Card
SPD0001	Surge Protective Device, 110-120V

<b>P/N</b> 40C2300	<b>Furniture</b> Adjustable Stand
-----------------------	--------------------------------------

Supports up to four optional 550-sheet trays.  
 All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at [http://www.lexmark.com/publications/furniture\\_safety/](http://www.lexmark.com/publications/furniture_safety/)  
 IPDS License and Bar Code License require an Intelligent Storage Drive.

Product Specifications		Lexmark CX730de
<b>Printing</b>		
Display	58xmark e-Task 7-inch (17.8 cm) color touch s6B8A	
Print Speed	Up to: Black: 42 ppm <sup>1</sup> (L8G8E) / Color: 42 ppm <sup>1</sup> (L8G8E)	
Time to First P4:8	As f4F t as: Black: 6.4 s86onds / Color: 7.0 s86BA7F	
Print R8FB7HG<BA	Black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi) / Color: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi	
% 8@BEL	+GA74E d: 2048 MB / Maximum: 2048 MB	
4E d Disk	!AGelligent StBEage Drive (BC tional); Magnetic Hard Disk (BC tional)	
* 86ommeded Monthly Page VB7H@8	1500 - 15000 pages <sup>2</sup>	
% aximum Monthly Duty CL678	Up to: 120000 pages per month <sup>3</sup>	
<b>Copying</b>		
CBCy Speed	Up to: Black: 42 cpm <sup>1</sup> (L8G8E) / Color: 42 cpm <sup>1</sup> (L8G8E)	
Time to First CBCL	As f4F t as: Black: 6.7 s86onds / Color: 7.3 s86BA7F	
<b>Scanning</b>		
+6anner Type / ADF Sc4A	Flatbed s6anner with ADF / DADF (single pass Duplex)	
A4/Ltr Duplex Scan Speed	Up to: Black: 80 / 84 sides per minute / Color: 80 / 84 sides per minut8	
A4/Ltr Simplex Scan Speed	Up to: Black: 40 / 42 sides per minute / Color: 40 / 42 sides per minut8	
ADF Paper Input C4C46<CL	Up to: 100 pages 20 lb or 75 gsm bond	
<b>Supplies<sup>4</sup></b>		
S4F er C4Etridge Y<877F	up to: 10,500 <sup>5</sup> -page Color (CM1) High Yield C4Etridges / up to: 22 000 <sup>5</sup> -page Black High Yield C4EGE<7:8	
Imaging Unit EsG<@46d Y<877	Up to: 150000 pages, based on 3 av8Eage lett8E/A4-size pages per print job and ~ 5% c8I 8E4:8 <sup>6</sup>	
C4Etridge(F) Shipping with PrB7H6G	5 000 <sup>5</sup> -page (CM1# ) Return PrB: am Toner C4EGE<7:8F <sup>5</sup>	
<b>Paper Handling</b>		
Included Paper Handling	100-Sheet MH7G<CHEC8F F8878E, Int8:E 4Ged DupleK, 300-Sheet Output Bin, 550-Sheet Input	
'C tional Paper Handling	550-Sheet TE4L	
( aper Input C4C46<CL	Up to: +GA74E d: 650 pages 20 lb or 75 gsm bond / Maximum: 2850 pages 20 lb or 75 gsm bond	
( aper Output C4C46<CL	Up to: +GA74E d: 300 pages 20 lb or 75 gsm bond / Maximum: 300 pages 20 lb or 75 gsm bond	
% edia Types Suppor87	. <A/I Labels, Banner P4C8E, Paper Labels, C4Ed StB6>, Plain P4C8E, Enl elopes, R89er to the Paper & Specialty Media Guide	
% edia Sizes Suppor87	A6, Oficio, 7 3/4 Enl 87BC8, 9 Enl 87BC8, JIS-B5, A4, Legal, A5, L8G8E, B5 Enl 87BC8, St4G8@8AG, C5 Enl 87BC8, Ex86HG<8, Univ8EFal, DL Enl 87BC8, FB7<8 10 Enl 87BC8	
<b>General Information<sup>7</sup></b>		
+GA74E d PBEGF	Gigabit Ethernet (10/100/1000), FEont USB 2.0 Specification Hi-Speed C8Etified port (, ype A), Rear Hi-Speed USB PBET Compatible with USB 2.0 Specification (, ype A), USB 2.0 Specification Hi-Speed C8Etified (, ype B), One Internal C4Ed SloG	
'C tional NetU ork PBEGF	!AGernal MarkNet N8370 802.11b/g/n/a Wireless, NFC	
&B<Fe L8I 87	'C8E ating: 52 dBA (Print) / 55 dBA (CBCy) / 51 dBA (+6an)	
Specified Operating Enl<BA@8AG	H@<7<G: 8 to 80% R874G<8 Humidity / T8<C8E 4GH8: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 M8Gers (9,500 F88G)	
S<@<8d W4EEAAGL	See St4Gement of Limited W4EEAAGy: 1-1 ear Onsite Serl<68, Nekt Business D4L	
+<8 / W8<;G	H x W x D: 24.44 x 18.85 x 20.9 in. / 85.98 lb.	
ENERGY S, AR TLC<6al ElectricitL	TEC: 0.55 kiloJ 4GGhours per w88>	
CBAFH<C G<BA		

All information is subject to change without noG<8. L8xmark is not liable for any errors or omissions.

<sup>1</sup> Print and CBCy speeds measured in ac6BE74A6 e with ISO/IEC 24734 and ISO/IEC 24735 r8FC86G<lely (ESA, ). For more information see: wJ J .leK@4E>.6om/ISOspeeds.  
<sup>2</sup> "R86ommeded Monthly Page Volume" is a range of pages that helps cus8mers el47H4G8 L8K@4E>8 product o99erings based on the av8Eage number of pages cus8mers plan t8 print on the del<6e each month. L8xmark r86ommeds that the number of pages per month be within the sG8Ged range for optimum del<6e per9BE@4A6 8, based on f46Gors including: supplies r8C746ement int8EI als, paper loading int8EI als, speed, and tLC<6al cus8mer us4:8 .<sup>3</sup> "Maximum Monthly Duty CLcle" is defined as the maximum number of pages a del<68 could deliver in a month using a multishift operation. This metric prBvides a cB@C4E<Fon of rB5HFtness in relation to other L8xmark printers and MFPs. <sup>4</sup> (E oduct functions only with BC746ement c4Etridges designed for use in a specific geogr4C;<6 al region. See wJ J .leK@4E>.6om/regions for more details. <sup>5</sup> Al 8Eage continuous black or continuous cB@CBF<C8 CM1 78674Eed c4Etridge yield up to this number of sGA74E d pages in ac6BE74A6 e with ISO/IEC 19798. <sup>6</sup> Actual Yield may v4Ey based on other f46Gors such as del<6e speed, paper size and 9eed orientation, toner c8I 8E4:8 , tray s8HE68, per68ACage of black-only printing and av8Eage print job cB@C78 K<G <sup>7</sup> (E<A@rs are sold subject to c8EGain lic8AF8/agreement conditions. See wJ J .leK@4E>.6om/print8E7<8AFE for details.

# Printzone.

## 1300 782 636

This is a Class A del<6e ac6BE8ding to international electromagnetic emissions sGA74E ds (i.8. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-7B@8F tic enl<6onments. Use of a Class A product in residential/domestic enl<6onments may c4HF8 int8E98E8A6e to radio cB@HA<6ations and r8DH<8 c8EB86G<8 measures.

© 2022 L exmark . All rights r eserved.

Lexmark , the L exmark logo and Unis onar e tr ademark s of L exmark Int ernational, Inc ., r egis tered in the Unit ed S tat es and/or o ther c ountries .

Apple and AirPrint ar e tr ademark s of Apple Inc ., r egis tered in the U .S. and o ther c ountries and r egions . M OPRIA ; the M opria™ L ogo , and the M opria Allianc e™ word mark and logo ar e r egis tered and/or un r egis tered trademark s and service mark s of M opria Allianc e, Inc . in the Unit ed S tat es and o ther c ountries . Unauthor ed us e is s trictly pr ohibit ed. ENER GY STAR and the ENER GY S TAR mark ar e r egis tered tr ademark s ow ned b y the U .S. Environm ent al Pr otection A gency . EPE AT is a tr ademark o f the Gr een Electr onics C ouncil in the Unit ed Stat es and o ther c ountries . PANT ONE™ is the pr oper ty of P ant one LL C. All o ther tr ademark s ar e the pr oper ty of their r espectiv e ow ners .

This pr oduct includes s oftwar e de veloped b y the OpenS SL Pr oject f or us e in the Open S SL T oolkit (<http://www.openssl.org/>).

