

Lexmark MC3326i

Small. Dependable. Secure.

Compact and lightweight, the Lexmark MC3326i multifunction brings colour printing, automatic scanning, copying, available cloud faxing* and touch-screen convenience to small workgroups. Output at up to 24 pages per minute** and high-yield replacement print cartridges keep the work moving. And Wi-Fi, one-piece print cartridges, gigabit ethernet and Lexmark full-spectrum security are all standard.



Compact colour versatility

- ▶ Get colour output at up to 24 pages per minute**, plus automatic-feed single-side scanning and available cloud faxing*.
- ▶ Tackle your printing workload with the power of a 1-GHz processor and 512 MB of memory.
- ▶ Connect via standard Wi-Fi, gigabit ethernet and USB.
- ▶ Simplify mobile printing via Lexmark Mobile Print app, as well as Mopria® and AirPrint technologies.
- ▶ 7.2 cm touch screen offers built-in workflow capabilities like scan to network, scan to e-mail and Lexmark's own Cloud Connector.

Easy to set up, easy to keep going

- ▶ Compact dimensions 344.4 mm high x 411.2 mm wide x 394.1 mm deep helps it fit almost anywhere.
- ▶ Unison™ Toner replacement cartridges deliver up to 2500

colour pages*** and 3000 monochrome pages** of high-quality output.

- ▶ Steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.

Built for planet earth

- ▶ Built-in energy-saving mode goes from sleep to print to sleep with nothing to set.
- ▶ Printer is rated EPEAT® Silver**** and is ENERGY STAR® certified.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).



* Subject to subscription with etherFAX®. A trial package (up to 3 months or 300 pages, whichever comes first) is included free of subscription charge; other fees, such as telecommunication charges, may apply. Contact etherFAX (www.etherfax.net) for details. Trial may be withdrawn without notice. Service may not be available in all locations.

** Analogue faxing via phone line is not supported by this device.
** Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

*** Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

**** EPEAT ratings may vary by location. See www.epeat.net for registration status by country.

Product Specifications		Lexmark MC3326i
Printing		
Display	2.8 inch (7.2 cm) Color touch s4G6?	
Print Speed	Up to: Black: 24 ppm ¹ (A4) / Colour: 24 ppm ¹ (A4)	
Time to First P286	as f2Dt as: Black: 10.6 s64onds / Colour: 10.6 s64@75D	
Print R6D@=FE:@?	Black: 4800 CQ (2400 x 600 dpi) / Colour: 4800 CQ (2400 x 600 dpi)	
% 6>@CJ	+E2752C d: 512 MB / Maximum: 512 MB	
2C d Disk	&@t AG2:=23=6	
* 64ommeded Monthly Page V@=F>6	600 - 2500 pages ²	
% aximum Monthly Duty CJ4=6	Up to: 50000 pages per month ³	
Copying		
C@Ay Speed	Up to: Black: 24.7 cpm ¹ (A4) / Colour: 24.7 cpm ¹ (A4)	
Time to First C@AJ	as f2Dt as: Black: 13.1 s64onds / Colour: 13.1 s64@75D	
Scanning		
+4anner Type / ADF Sc2?	Flatbed s4anner with automatic document feeder / One-sided automatic document f6656C	
A4/Ltr Simplex Scan Speed / Sc2?	Up to: Black: 20 / 21 sides per minute / C@=FE 20 / 21 sides per minut6	
Speed (A4/LEC		
ADF Paper Input C2A24:E J	Up to: 50 pages 75 gsm bond	
Supplies ⁴		
s2Der C2Ctridge Y6=5D	up to: 2,500 ⁵ -page Colour (CM1) High Yield C2Ctridges / up to: 3 000 ⁵ -page Black High Yield C2Ctridge / up to: 1,500 ⁵ -page Black and Colour (CM1#) C2CEC:586D	
C2Ctridge(D) Shipping with Pr@5F4E	750 ⁵ -page Black Return Pr@8Cam Toner C2CEC:586, 500 ⁵ -page Color (CM1) Return Pr@8Cam Toner C2CEC:586	
Paper Handling		
Included Paper Handling	100-Sheet Output Bin, Single-Sheet Manual Feed, AFEomatic 2-sided printing, 250-Sheet Input	
(aper Input C2A24:E J	Up to: +E2752C d: 250+1 pages 75 gsm bond / Maximum: 250+1 pages 75 gsm bond	
(aper Output C2A24:E J	Up to: +E2752C d: 100 pages 75 gsm bond / Maximum: 100 pages 75 gsm bond	
% edia Types Support65	Hagaki C2Cd, Paper Labels, C2Cd St@4< Plain P2A6C, Glossy paper, R67er to the Paper & Specialty Media Guide	
% edia Sizes Suppor65	A6, Oficio, 7 3/4 EnG6=@A6 9 EnG6=@A6 JIS-B5, A4, Legal, A5, Hagaki C2Cd, L6E6C B5 EnG6=@A6 St2E6>67E , C5 EnG6=@A6 Ex64FE:G6 -?:G 6C6l, DL EnG6=@A6 F@=:@10 EnG6=@A6	
General Information ⁶		
+E2752C d P@ED	F@ont Hi-Speed USB port Compatible with USB 2.0 Specification (, ype A), 802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed C6Ctified (, ype B), Ethernet 10/100/1000 Bas6, X (R"-45)	
&@:De L6G6=	'A6C ating: 50 dBA (Print) / 50 dBA (C@Ay) / 44 dBA (+4an)	
Specified Operating EnG:@?>6?E	F>:5:E y: 8 to 80% R6=2E@ Humidity / Altitude: 0 - 3048 metres / T6>A6C 2EFCe: 10 to 32°C (50 to 90°F)	
(Coduct W2CQ?E J	1- Year Onsite R6A2:C, Nel t Business D2J	
+;Ke / W6:89E	H x W x D: 344.4 x 411.2 x 394.1 mm / 19.4 k8	
ENERGY S, AR TJA:4 al ElectricitJ	TEC: 0.35 kiloh 2EE-hours per w66<	
C@7DF>A E:@?		

All information is subject to change without noE:46. L6xmark is not liable for any errors or omissions.

¹ Print and c@Ay speeds measured in ac4@G274 e with ISO/IEC 24734 and ISO/IEC 24735 r6DA64EEgely (ESA,). For more information see: wHH.l6l>2C< .4om/ISOspeeds.

² "R64ommeded Monthly Page Volume" is a range of pages that helps cusEomers eG2=F2Ee L6l>2C< 6 product o7terings based on the av6Cage number of pages cusEomers plan Eo print on the deG:4e each month. L6xmark r64ommeds that the number of pages per month be within the sE2Eed range for optimum deG:4e per7@C>274 6, based on f24E@CD including: supplies r6A=24ement int6CGals, paper loading int6CGals, speed, and tJA:4 al cusEomer us286 . ³ "Maximum Monthly Duty CJcle" is defined as the maximum number o7 pages a deG:4e could deliver in a month using a multishift operation. This metric pr@vides a c@>A2C:Don of r@3FDtness in relation to other L6xmark printers and MFPS. ⁴ (C@5F4E functions only with r6A=24ement c2Ctridges designed for use in a specific geogr2A9:4 al region. See wHH.l6l>2C< .4om/regions for more details. ⁵ AG6Cage continuous c2CEC:586 yield is sE2Eed number of sE2752C d pages as lisEed. D64=2@d yield value in ac4@G274 e with ISO/IEC 19798. ⁶ (C?:E ers are sold subject to c6CEain lic67D6/agreement conditions. See wHH.l6l>2C< .4om/print6C=-67De for details.

Printzone.
1300 782 636